

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 241 513 A1

(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 158(3) EPC

(43) Date of publication:
18.09.2002 Bulletin 2002/38

(51) Int Cl.7: **G02F 1/01**

(21) Application number: 00971725.7

(86) International application number:
PCT/JP00/07699

(22) Date of filing: 01.11.2000

(87) International publication number:
WO 01/044863 (21.06.2001 Gazette 2001/25)

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR

(30) Priority: 14.12.1999 JP 35487199

(71) Applicants:
• Japan Science and Technology Corporation
Kawaguchi-shi, Saitama 332-0012 (JP)
• Citizen Watch Co. Ltd.
Tokyo 188-8511 (JP)

• YAMASHITA, Mikio
Sapporo-shi, Hokkaido 003-0021 (JP)
• SUGURU, Akira
Kawagoe-shi, Saitama 350-1141 (JP)
• MOROKAWA, Shigeru
Higashiyamato-shi, Tokyo 207-0002 (JP)


(72) Inventors:
• MORITA, Ryuji
Sapporo-shi, Hokkaido 001-0027 (JP)

(74) Representative:
Röhl, Wolf Horst, Dipl.-Phys., Dr. et al
Sparing-Röhl-Henseler
Patentanwälte
Postfach 14 04 43
40074 Düsseldorf (DE)

(54) **ULTRABROAD-BAND VARIABLE-WAVELENGTH WAVELENGTH-MULTIPLEXED PULSE WAVEFORM SHAPING DEVICE**

(57) An ultra-broadband, variable and multiple wavelength, waveform shaping apparatus is disclosed that excels with the ability to yield light pulses shaped in waveform, variable and multiple in wavelength over an ultra-broad bandwidth, the pulses being as short as in the order of pico-seconds or less, or even in the order of femto-seconds. The apparatus includes a light source (21) for a light pulse, an ultra-broadband light pulse generating unit (22) for producing from a light pulse, an ultra-broadband light pulse beam, a beam expander (24) for spatially expanding the beam in one direction (along the y-axis) in its cross section, and a wavelength dispersive unit (26) for dispersing wavelengths of light beam pulse while further spatially expanding the expanded beam along the x-axis, a two-dimensional spatial amplitude modulator (11) for selecting wavelength bands varying in center frequency along the y-axis, a two-dimensional space phase amplifier (12) for modulating a plurality of lights selected by wavelengths into different phases, and a beam reducing and waveform shaping unit (28) for reducing so phase modulated light beam pulse components along the x-axis while shaping them into desired waveforms, whereby multiple wavelength light pulses are formed, which have center their wavelengths varying along the y-axis and waveforms shaped independently of each other and as desired.

FIG. 1



Description

Technical Field

[0001] The present invention relates to an ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus for use in an optical pulse generator for generating light pulses variable and multiple in wavelength over an ultra-broad bandwidth, i.e., a pulse waveform shaping apparatus for shaping light pulses variable and multiple in wavelength over an ultra-broad bandwidth, in which an ultra-broadband light pulse is produced and is then subjected to two-dimensional modulations both in amplitude and phase effected in a beam of the light pulse.

Background Art

[0002] Light pulse waveform shaping has hitherto been performed by passing a light pulse having a single preselected center wavelength through either a one-dimensional spatial phase modulator or a one-dimensional spatial amplitude modulator or a combination of the two, or passing a light pulse having a single preselected center wavelength through a two-dimensional spatial phase modulator.

[0003] Light pulse waveform shaping of this type is designed to shape the waveform of a light pulse having a single preselected center wavelength by using a dispersing element to spatially expand the light pulse in dependence on its wavelengths and to effect a phase or an amplitude modulation for each of its wavelength components.

[0004] As the literature for the case of using a one-dimensional spatial phase modulator and for the case of using a one-dimensional spatial amplitude modulator, here may be cited "A. M. Weiner, J. P. Heritage and E. M. Kirschner, J. Opt. Soc. Am. B5, 1563 (1988)".

[0005] Also, as the literature for the case of using both of them, here can be cited "M. M. Wefers and K. A. Nelson, Opt. Lett. 18, 2032 (1993)".

[0006] Further, as the literature for the case of using a two-dimensional spatial phase modulator, here may be cited "M. M. Wefers, K. A. Nelson and A. M. Weiners, Opt. Lett. 21, 746 (1996)".

[0007] In the instances shown in the past literature cited above, however, the use of either a one-dimensional spatial phase modulator or a one-dimensional spatial amplitude modulator or even the use of both of them permitted only light pulses of the single center wavelength shaped in waveform to be obtained.

[0008] On the other hand, the instance of using a two-dimensional spatial phase modulator made it possible to obtain light pulses varying in waveform with their spatial positions but having the same one wavelength, and thus again permitted only light pulses of the single center wavelength shaped in waveform to be obtained.

[0009] In view of the problem noted above, the

present invention is aimed to provide an ultra-broadband, variable and multiple wavelength, waveform shaping apparatus that excels with the ability to yield light pulses shaped in waveform, variable and multiple in wavelength over an ultra-broad bandwidth, the pulses being as short as in the order of pico-seconds or less, or even in the order of femto-seconds.

DISCLOSURE THE INVENTION

[0010] In order to achieve the object mentioned above, the present invention provides as set forth in claim 1 in the appended claims an ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus of the type to provide optical pulses shaped in waveform, characterized in that it comprises: an ultra-broadband light pulse generating means for receiving from a light source a fundamental wave light pulse having a bandwidth and broadening the bandwidth of said fundamental wave light pulse into an ultra-broadband range to produce an ultra-broadband light pulse; a beam expander means for spatially expanding a beam of the said ultra-broadband light pulse in a direction in a cross section thereof to form an expanded beam of ultra-broadband light pulse; and a wavelength dispersive means for dispersing wavelengths of the ultra-broadband light pulse of the said expanded beam while further spatially expanding the said expanded beam in another direction in a cross section thereof, thereby forming an ultra-broadband light pulse with a beam cross section expanded two-dimensionally.

[0011] In addition to the makeup mentioned above, the apparatus as set forth in claim 2 in the appended claims may be characterized in that it further includes a two-dimensional spatial amplitude modulator for selecting wavelength bands varying in center frequency along one direction in the ultra-broadband light pulse with the beam cross section expanded two-dimensionally; and a two-dimensional spatial phase modulator for modulating a plurality of light components so selected by wavelength into different phases, whereby light pulses shaped in waveform and variable and multiple in wavelength are formed.

[0012] The apparatus as set forth in claim 3 in the appended claims may also be characterized in that it further includes a beam reducing and waveform shaping means for reducing a two-dimensionally amplitude- and phase-modulated ultra-broadband light pulse component and shaping it into a desired waveform.

[0013] The apparatus as set forth in claim 4 in the appended claims may also be characterized in that the said beam reducing and waveform shaping means comprises at least one of a cylindrical lens and a cylindrical mirror.

[0014] The apparatus as set forth in claim 5 in the appended claims may also be characterized in that the said beam reducing and waveform shaping means comprises at least one of a diffraction grating and a prism,

on the both.

[0015] The present invention also provides as set forth in claim 6 in the appended claims an ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus characterized in that an ultra-broadband light pulse generated on the basis of a fundamental wave light pulse from a light source has its beam cross section spatially expanded, and its wavelengths dispersed, in one direction in the said beam cross section by at least one of a pair of cylindrical lenses and a pair of cylindrical mirrors and in another direction perpendicular to the said one direction by at least one of a diffraction grating and a prism, respectively; the ultra-broadband light pulse having been expanded is collimated by either a cylindrical lens or a cylindrical mirror; the collimated ultra-broadband light pulse is applied to a two-dimensional spatial amplitude modulator for selection of wavelength bands varying in center wavelength along the said one direction; the selected center wavelength light is applied to a two-dimensional spatial phase modulator and a plurality of light components so selected by wavelength is modulated into different phases, respectively, to produce light pulses shaped in waveform and variable and multiple in wavelength.

[0016] The apparatus so defined in the preceding paragraph may further be characterized as set forth in claim 7 in that an ultra-broadband light pulse modulated by both the said two-dimensional spatial amplitude and phase modulators is reduced in beam cross section by at least one of a cylindrical lens and a cylindrical mirror on the both, or at least one of a diffraction grating and a prism on the both, and thereby is shaped into a desired waveform.

[0017] The apparatus as set forth in claim 8 in the appended claims may also be characterized in that the said two-dimensional spatial amplitude modulator and the said two-dimensional spatial phase modulator are each subjected to a feedback control so as to provide desired pulses.

[0018] The apparatus as set forth in claim 9 in the appended claims may also be characterized in that the said light source is a pulse laser generator of providing an ultra-short pulse of pico-seconds or less.

[0019] The apparatus as set forth in claim 10 in the appended claims may also be characterized in that the said light source for generating the fundamental wave light pulse is any one of a solid state laser, a fiber laser, a semiconductor laser, a dye laser and an optical parametric laser, or a combination thereof with an amplifier system.

[0020] The apparatus as set forth in claim 11 in the appended claims may also be characterized in that the said ultra-broadband light pulse producing means includes at least one nonlinear optical medium adapted for the said fundamental wave light pulse to be passed therethrough.

[0021] The apparatus as set forth in claim 12 in the appended claims may also be characterized in that the

said ultra-broadband light pulse is a light pulse in an ultra-broadband and having a pulse duration of pico-seconds or less.

[0022] The apparatus as set forth in claim 13 in the appended claims may also be characterized in that the said nonlinear optical medium is a hollow fiber filled with either a gas or an ionized gas.

[0023] The apparatus as set forth in claim 14 in the appended claims may also be characterized in that the said nonlinear optical medium is made of any one of a waveguide structure, a bulk structure, a thin film structure, a photonic crystalline structure, a photonic fiber and a liquid, or an optical combination of two or more thereof.

[0024] The apparatus as set forth in claim 15 in the appended claims may also be characterized in that the said nonlinear optical medium has a third-order nonlinear optical property.

[0025] The apparatus as set forth in claim 16 in the appended claims may also be characterized in that the said two-dimensional spatial amplitude modulator includes a two-dimensional space filter for selecting different center amplitudes from the ultra-broadband light pulse.

[0026] The apparatus as set forth in claim 17 in the appended claims may also be characterized in that the said two-dimensional spatial amplitude modulator comprises a first ultra-broadband polarizing plate, a two-dimensional spatial phase modulator, and a second ultra-broadband polarizing plate of which the polarization axis is perpendicular to the polarization axis of the said first polarizing plate.

[0027] The present invention by taking a makeup as mentioned above makes it possible to produce a plurality of optical pulse trains variable and multiple in wavelength, each independently of another and simultaneously or synchronously with another.

[0028] If such light pulses variable in wavelength and shaped with waveforms as desired are used and a material is irradiated with those light pulses with controlled wavelengths adequate to cause the electron energy level resonance and controlled time intervals in such a shaped train of pulses adequate to cause the vibrational energy level resonance, it is made possible to effect what is called multi-dimensional, electron energy level and vibrational energy level dual and selective excitation, thereby to pave the way for application to the control of a chemical reaction and also to growth control.

BRIEF DESCRIPTION OF THE DRAWINGS

[0029] The present invention will better be understood from the following detailed description and the drawings attached hereto showing certain illustrative forms of embodiment of the present invention; in this connection, it should be noted that such forms of embodiment illustrated in the accompanying drawings hereof are intended in no way to limit the present invention but to facilitate

an explanation and understanding thereof. In the drawings:

Fig. 1 is a makeup view diagrammatically illustrating one form of embodiment of the present invention; Fig. 2 illustrates further arrangements that may be adopted in embodying the ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus of the present invention, including Fig. 2a that is a makeup view of the arrangement in which the first ultra-broadband light pulse generating unit has at its light incoming side a second ultra-broadband light pulse generating unit and Fig. 2b that is a makeup view of the arrangement in which the first ultra-broadband light pulse generating unit has at its light outgoing side a second ultra-broadband light pulse generating unit;

Fig. 3 conceptionally illustrates the makeup of a two-dimensional spatial amplitude modulator for use in the form of embodiment illustrated and includes Fig. 3a that illustrates in a conceptional view a two-dimensional space filter and Fig. 3b that illustrates in a spectrum view the wavelength cutout; Fig. 4 conceptionally illustrates the makeup of another two-dimensional spatial amplitude modulator for use in the form of embodiment illustrated and includes Fig. 4a that illustrates in a conceptional view the makeup of another two-dimensional spatial filter, Fig. 4b that illustrates an ultra-broadband polarizing plate, Fig. 4c that illustrates a two-dimensional spatial phase modulator and Fig. 4d that illustrates another ultra-broadband polarizing plate; Fig. 5 diagrammatically illustrates the cross section of an ultra-broadband light pulse beam each after passing through a certain optical element in the present form of embodiment wherein Fig. 5(a) shows a light pulse beam outgoing from a spherical lens 5, Fig. 5(b) shows the cross section of a light pulse beam outgoing from a cylindrical lens for expanding the light pulse beam in its cross section in one direction and Fig. 5(c) shows the cross section of a light pulse beam outgoing from an entrance diffraction grating;

Fig. 6 illustrates a light pulse beam with a two-dimensional spread according to the illustrated form of embodiment wherein Fig. 6(a) is a beam cross sectional view of the ultra-broadband light beam and Fig. 6(b) is a diagram showing a spectral distribution $S(\lambda)$ of the ultra-broadband light beam;

Fig. 7 illustrates the wavelength cutout function of the two-dimensional spatial amplitude modulator in the illustrated form of embodiment wherein Fig. 7(a) is a diagram illustrating how the amplitude modulation by the two-dimensional spatial amplitude modulator is effected, and Fig. 7(b) is a diagram illustrating the spectral distribution $S(\lambda)$ after the cutout of wavelengths is effected by way of the amplitude modulation by the two-dimensional spatial

amplitude modulator; and

Fig. 8 illustrates the independent waveform shaping function by the two-dimensional spatial phase modulator in the illustrated form of embodiment wherein Fig. 8(a) is a diagram illustrating how phase modulation by the two-dimensional spatial phase modulator is effected, Fig. 8(b) is a cross sectional view of the beam outgoing from an exit diffraction grating, and Fig. 8(c) is a diagram illustrating pulses independently shaped in waveform and having different center wavelengths (ultra-broadband, variable wavelength, multiple wavelength, waveform shaped pulses).

Best Modes for Carrying out the Invention

[0030] Hereinafter, an explanation is given in respect of suitable forms of embodiment of the ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus of the present invention.

[0031] Fig. 1 is a makeup view diagrammatically illustrating one form of embodiment of the ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus of the present invention.

[0032] Referring to Fig. 1, this form of embodiment of the ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus of the present invention, indicated by reference character 20, includes a light source 21 for generating an ultra-short light pulse that is short as in the order of pico-seconds or less, a first ultra-broadband light pulse generating unit 22 for broadening the bandwidth of the light pulse to produce an ultra-broadband light pulse in the form of a beam, a beam expander 24 for spatially expanding the beam of this ultra-broadband light pulse in a direction (which is here assumed to be along a y-axis) in a cross section of the beam to form an expanded beam of ultra-broadband light pulse, and a wavelength-dispersive unit 26 for dispersing wavelengths of the ultra-broadband light pulse of the expanded beam, while further expanding the beam, in another direction in a cross section of the beam, thereby forming an ultra-broadband light pulse with a beam cross section expanded two-dimensionally.

[0033] Here, the term "beam cross section" is used to refer to a cross section of the beam cut perpendicular to the direction in which the ultra-broadband light pulse propagates.

[0034] For the light source 21, use may be made of a laser system of any one of a solid-state laser, a fiber laser, a semiconductor laser, a dye laser and an optical parametric laser, or such a laser system combined with an amplifier system.

[0035] Also, for the first ultra-broadband light pulse generating unit 22 shown in Fig. 1, use is here made of a pressure chamber 3 filled with a gas, e.g., a rare gas and having a hollow fiber 4 disposed therein aligned with the optical axis of the laser system and the unit, but may be made simply of such a hollow fiber 4 alone that is

filled with a rare gas and aligned with the optical axis.

[0036] Further, instead of a rare gas, the pressure chamber 3 may be held filled with an ionized gas produced, e.g., by applying a voltage across a pair of electrodes disposed at the opposite ends of the chamber 3 so that the hollow chamber 4 disposed therein can also be held filled with the ionized gas. Alternatively, the hollow fiber 4 alone may again be used that is aligned with the optical axis and here held filled with an ionized gas. The rare gas as the filler may also be replaced with a liquid.

[0037] The first ultra-broadband light pulse generating unit 22 is also shown to include an optical component such as a spherical lens 2 to condense the light pulse, and a collimator 5 that collimates the condensed light pulse, although they may be disposed separately outside of the unit.

[0038] Fig. 2 illustrates further arrangements that may be adopted in embodying the ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus of the present invention, including Fig. 2a that is a makeup view of the arrangement in which the first ultra-broadband light pulse generating unit has at its light incoming side a second ultra-broadband light pulse generating unit and Fig. 2b that is a makeup view of the arrangement in which the first ultra-broadband light pulse generating unit has at its light outgoing side a second ultra-broadband light pulse generating unit.

[0039] While ultra-broadband light pulse generating units, shown in Figs. 2a and 2b and indicated by reference character 42 (and 44), respectively, are each a combination of the ultra-broadband light pulse generating unit 22 shown in Fig. 1 with the second ultra-broadband light pulse generating unit, indicated by reference character 32, the first ultra-broadband light pulse generating unit 22 in Fig. 1 may be replaced with the second ultra-broadband light pulse generating unit 32 alone.

[0040] The second ultra-broadband light pulse generating unit 32 shown in Fig. 2 includes a condensing element 34 and a collimator 38 and has a separate nonlinear optical medium structure 36 disposed on the optical axis between them. It should be noted in this connection that the hollow fiber 4 filled with a rare gas or ionized gas is an example of the nonlinear optical medium structure.

[0041] An ultra-broadband light pulse is obtainable when a fundamental wave pulse from a laser light source having a selected center wavelength is passed through a nonlinear optical medium to bring about a self-phase modulation effect and thereby to result in an expanded spectrum, or to bring about an induced phase modulation effect between such a fundamental wave pulse and a pulse generated by a nonlinear phenomenon that takes place using the fundamental wave pulse and thereby to result in an expanded spectrum. For the nonlinear optical medium, use may be made of many an inorganic or organic material that is large in the third-order nonlinear optical property. For the nonlinear opti-

cal medium structure, use may be made of a waveguide structure, a bulk structure, a thin film, a photonic crystalline structure, a photonic fiber structure or a liquid.

[0042] For the waveguide structure, any structure is sufficient if it can confine a light therein, and it may be a fiber or channel waveguide structure. For the bulk or the thin film, which is a structure that cannot confine a light therein but let it spread, but which can be formed from any material even though it is poor in machinability, use may thus be made of any inorganic or organic material that is large in the third-order nonlinear optical property. A photonic crystal is a structure in which atoms are arranged regularly with a period in the order of a light wavelength and is capable confining a light therein. A liquid if used may be filled in a transparent vessel.

[0043] In a most preferred form of embodiment of the present invention, as shown in connection with the first ultra-wideband light pulse generating unit the medium is a rare gas and the structure is a hollow fiber filled with a rare gas, and it is made of glass to form a waveguide structure.

[0044] The wavelength dispersive unit 26 in the form of embodiment illustrated may include a collimator in the form of a cylindrical lens or mirror, although they may be separately disposed outside of the unit.

[0045] The ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus 20 in the illustrated form of embodiment of the present invention further includes a two-dimensional spatial amplitude modulator 11 for selecting along the y-axis, different wavelength ranges with their respective center wavelengths, of the light pulse beam expanded two-dimensionally, a two-dimensional spatial amplitude modulator 12 for phase-modulating a plurality of light components in the selected wavelength ranges individually, and a beam reducing and waveform shaping unit 28 for reducing the phase-modulated light pulse beam in the direction of x-axis in its beam cross section while shaping it into any waveform as desired to form a multiple wavelength light pulse shaped in waveform. While its detailed explanation is to be given later, for the condensing element use may be made of a cylindrical lens or mirror, and for the pulse waveform shaping section use may be a diffraction grating.

[0046] Fig. 3 conceptionally illustrates the makeup of a two-dimensional spatial amplitude modulator for use in the form of embodiment illustrated and includes Fig. 3a that illustrates in a conceptional view a two-dimensional space filter and Fig. 3b that illustrates in a spectrum view the cutout of wavelengths. As shown in Fig. 3, the two-dimensional spatial amplitude modulator has a two-dimensional space filter 50, e.g., with an array of pixels being 648 (in the direction of x-axis) x 4 (in the direction of y-axis) in number, which is provided with regions 54 transparent, and regions 52 nontransparent to, the light pulse beam. Thus, passing the ultra-broadband light pulse through the 2-dimensional space filter 50 allows different center wavelengths as shown in Fig. 3b

to be selected and in effect the wavelengths to be cut out.

[0047] Fig. 4 conceptionally illustrates the makeup of another two-dimensional spatial amplitude modulator for use in the form of embodiment illustrated and includes Fig. 4a that illustrates in a conceptional view the makeup of another two-dimensional space filter, Fig. 4b that illustrates an ultra-broadband polarizing plate, Fig. 4c that illustrates a two-dimensional spatial phase modulator and Fig. 4d that illustrates another ultra-broadband polarizing plate.

[0048] The two-dimensional spatial amplitude modulator, 60, shown in Fig. 4 is formed with the first ultra-broadband polarizing plate, 62, the two-dimensional spatial phase modulator, 64, with an array of pixels being 648 (in the direction of x-axis) x 4 (in the direction of y-axis) in number and the second ultra-broadband polarizing plate, 66, having an axis of light polarization orthogonal to that of the first ultra-broadband polarizing plate 62, wherein the members 62, 64 and 66 are laid one on top of another. In this two-dimensional spatial amplitude modulator 60, varying the two-dimensional spatial phase modulator 64 in phase varies the amount of light transmitted through the two orthogonal ultra-broadband polarizing plates. This permits a two-dimensional amplitude modulation to be effected. Further, what is indicated by numeral 61 in Fig. 4a represents an ultra-broadband light pulse expanded two-dimensionally, and what is indicated by numeral 63 represents an ultra-broadband light pulse modulated in amplitude two-dimensionally. Also, indicated by the arrows in Figs. 4b and 4c are the directions of the polarization axes of those plates, the light having whose polarization direction is only transmissive.

[0049] Mention is next made of an operation of this form of embodiment of the invention.

[0050] In the ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus 20 made up as mentioned above, an ultra-broadband light pulse as short as pico-seconds or less is produced and used, which has wavelengths extending over an ultra-broadband between 500 nm and 1000 nm.

[0051] A beam of this ultra-broadband light pulse is spatially expanded in one direction of its cross section, say in the direction of y-axis, by using the beam expander 24, by such as a pair of cylindrical lenses or mirrors therein. The beam of ultra-broadband light pulse so spatially expanded is then subjected to wavelength dispersion and second spatial expansion both by the waveform dispersive unit 26 wherein it is spatially expanded in another direction in the same cross section orthogonal to that one section, say in the direction of an x-axis orthogonal to the y-axis.

[0052] The resulting ultra-broadband light pulse, then after having been collimated by the collimator such as a cylindrical lens or mirror in the wavelength dispersive unit 26, is subjected in the 2-dimensional spatial amplitude modulator 11 to selection or extraction of different

wavelength ranges with their respective center wavelengths (cutout of wavelengths) in the direction of y-axis. A resultant plurality of light components with the wavelengths selected is then phase—modulated by the 2-dimensional spatial phase modulator 12 into different phases.

[0053] A resultant ultra-broadband light pulse phase-modulated is reduced in its beam cross section in the direction of x-axis and thereafter shaped into a waveform as desired, both by the beam reducing and waveform shaping unit 28. Here, reducing the ultra-broadband light pulse in its beam cross section in the direction of x-axis corresponds to removing its spread in the direction of x-axis which it had when the wavelengths were dispersed. This makes it possible to derive light pulses with their center wavelengths varying depending on positions in the direction of y-axis and shaped with any waveform as desired and independently of one another, namely multiple wavelength light pulses shaped in wave form.

[0054] In this case, monitoring the center wavelength and waveform of each shaped pulse derived to effect feedback control allows the desired center wavelength and waveform to be obtained.

[0055] Mention is next made of a specific makeup of the abovementioned form of embodiment as well as effects and advantages thereof with reference to Figs. 1 and 5 to 8.

[0056] As mentioned previously, Fig. 1 is a conceptual makeup view showing one form of embodiment of the ultra-broadband variable and multiple wavelength pulse waveform shaping apparatus according to the present invention. The cylindrical lens has a curvature, and the diffraction grating has grooves, both along the y-axis.

[0057] Fig. 5 diagrammatically illustrates the cross section of an ultra-broadband light pulse beam each after passing through a certain optical element in the present form of embodiment wherein Fig. 5(a) shows a light pulse beam outgoing from the spherical lens 5, Fig. 5(b) shows the cross section of a light pulse beam outgoing from the cylindrical lens 6, 7 for expanding the light pulse beam in its cross section in one direction and Fig. 5(c) shows the cross section of a light pulse beam outgoing from the entrance diffraction grating 9.

[0058] Figs. 6, 7 and 8 show in explanatory views the wavelength cutout function of the two-dimensional spatial amplitude modulator and the independent waveform shaping function by the 2-dimensional spatial phase modulator.

[0059] Referring to Fig. 1, in the ultra-broadband variable and multiple wavelength pulse waveform shaping apparatus of the illustrated form of embodiment, a light pulse having a center wavelength of 790 nm, a pulse width of 30 fs, a pulse energy of 0.6 mJ and a repetition rate of 1 kHz is generated by a titanium-sapphire laser amplifier system as the light source 1. Then, using the spherical lens 2 having a focal length of 200 mm, the light pulse is condensed and guided into the ultra-broad-

band light pulse generating unit 22, which produces an ultra-broadband light pulse of a wavelength range of 500 to 1000 nm.

[0060] The ultra-broadband light pulse generating unit 22 is made of a pressure chamber 3 having, e.g., a sapphire made light inlet and outlet window and filled with argon at a pressure of 3.3 atm and a quartz made hollow fiber 4 having an inner diameter of 0.1 mm and a length of 300 mm. The ultra-broadband light pulse generating unit 22 is thus designed so that a light pulse condensed is received at the light entrance end of the quartz made hollow fiber 4.

[0061] The resultant ultra-broadband light pulse is then collimated by the spherical lens 5 having a focal length of 200 mm as the collimator, becoming a beam of light whose cross section is shown in Fig. 5(a). Then, the light beam is expanded in its cross section in the direction of y-axis by the beam expander unit 24 comprising the cylindrical lens 6 having a focal length of 20 mm and the cylindrical lens 7 having a focal length of 150 mm. The cross section of the expanded beam is shown in Fig. 5(b).

[0062] The light pulse beam expanded in the direction of y-axis, then after having been reflected by a planar mirror 8, is subjected to wavelength dispersion by the waveform dispersive unit comprising the entrance diffraction grating 9 having a grating constant of 600/mm, which expands the beam cross section in the direction of x-axis. The light so expanded is then collimated by the collimator comprising a cylindrical lens 10 having a curvature along the x-axis and a focal length of 150 mm.

[0063] The light pulse beam has now had a beam cross section that expands out two-dimensionally in both the directions of x- and y-axes as shown in Fig. 5 (c) also indicating that the direction of x-axis corresponds to that of the axis of wavelength λ , λ -axis. The relationship between the spread and the spectrum which the beam then has is indicated in Figs. 6(a) and 6(b). Here, Fig. 6(a) is a beam cross sectional view of the ultra-broadband light beam on the two-dimensional spatial amplitude modulator while Fig. 6(b) is a diagram showing a spectral distribution $S(\lambda)$ of the ultra-broadband light beam on the two-dimensional spatial amplitude modulator (indicating that the λ -axis is coincident with the x-axis in the beam cross section).

[0064] As shown in Figs. 6(a) and 6(b), while the beam cross section has the same wavelength components along the y-axis, it has wavelength components widely distributed along the x-axis corresponding to its spectral distribution $S(\lambda)$ since the direction of x-axis is coincident with that of the axis of wavelength λ .

[0065] This two-dimensionally spread light pulse is passed through the two-dimensional spatial amplitude modulator 11 having an array of pixels, for example, 648 (along the x-axis) x 4 (along the y-axis) in number. This array provides as shown in Fig. 7, four (y_1 , y_2 , y_3 and y_4 rows of) one-dimensional spatial amplitude modulators each of which comprises an array of pixels 648 x 1

within the cross section of the light pulse beam. If for these 1-st to 4-th rows of different amplitude modulations are applied, then wavelength components whose center wavelengths vary from one another, λ_1 , λ_2 , λ_3 and λ_4 , can be taken out (the cutout of wavelengths).

[0066] Here, Fig. 7(a) is a diagram illustrating how amplitude modulation by the two-dimensional spatial amplitude modulator is effected, while Fig. 7(b) is a diagram illustrating the spectral distribution $S(\lambda)$ after the cutout of wavelengths effected by way of amplitude modulation of the two-dimensional spatial amplitude modulator.

[0067] Then, the light pulse with its center wavelengths cut out that vary depending on positions along the y-axis is passed through the two-dimensional spatial phase modulator comprising an array of pixels 648 (along the x-axis) x 4 (along the y-axis) in number and having a maximum amount of phase modulation less than 2π , and thereby subjected to phase modulation for each of the y_1 row to the y_4 row. Then, the beam cross section as shown in Fig. 8(a) comes to have a phase modulation applied thereto for each of the pixels independently of one another. Here, Fig. 8(a) is a diagram illustrating how phase modulation by the two-dimensional spatial phase modulator is effected, Fig. 8(b) is a cross sectional view of the beam outgoing from an exit diffraction grating 14, and Fig. 8(c) is a diagram illustrating pulses independently shaped in waveform and having different center wavelengths (namely an ultra-broadband, variable wavelength, multiple wavelength, waveform shaped pulses).

[0068] Thereafter, by using the cylindrical lens 13 having a curvature along the x-axis and a focal distance of 150 mm, the light pulse beam is condensed on the diffraction grating 14 into the direction of x-axis. Then, the light pulse beam diffracted by the exit diffraction grating 14, whose beam cross section at this point of time is as shown in Fig. 8(b), provides a pulse shaped in waveform having a center frequency λ_1 at a position y_1 , a pulse shaped in waveform having a center frequency λ_2 at a position y_2 , a pulse shaped in waveform having a center frequency λ_3 at a position y_3 , and a pulse shaped in waveform having a center frequency λ_4 . Then, the respective pulse shaping patterns can be controlled each independently of one another to provide respective trains of pulses each of a waveform as desired. It is Fig. 8(c) which shows temporal waveforms of such independently shaped trains of pulses (which are shown in terms of pulse intensity versus time: $I(t)$).

[0069] Finally, a mirror 15 adjusts the directions in which ultra-broadband variable wavelength, wavelength multiple, waveform shaped pulses thus generated are to propagate.

[0070] Although the present invention has hereinbefore been set forth with respect to certain illustrative forms of embodiment thereof, it will readily be appreciated to be obvious to a person skilled in the art that many alternations thereof, omissions therefrom and additions

thereto can be made without departing from the essence and scope of the present invention. Accordingly, it should be understood that the invention is not intended to be limited to the specific forms of embodiment thereof set forth below, but to include all possible forms of embodiment thereof that can be made within the scope with respect to the features specifically set forth in the appended claims and encompasses all the equivalents thereof.

Industrial Applicability

[0071] An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus according to the present invention, with the use of a two-dimensional spatial amplitude modulator and a two-dimensional phase modulator, is capable of producing ultra-broadband light pulses, and generating a plurality of trains of optical pulses with wavelengths variable in an ultra-broadband, independently of one another but concurrently or even synchronously, and thus in a manner hitherto hard to effect. Accordingly, if a material is irradiated with such ultra-broadband light pulses with controlled wavelengths adequate to cause the electron energy level resonance and controlled time intervals in such a shaped train of pulses adequate to cause the vibrational energy level resonance, it is made possible to effect what is called multi-dimensional, electron energy level and vibrational energy level dual and selective excitation.

[0072] This makes it possible to control a reaction for a material, to control growth, to create a new material, to control a molecular function and to perform a selective excitation treatment.

[0073] The present invention is also applicable to optical information and transmission processing and optical computing by temporal, multiple wavelength and temporal parallel control and is thus extremely great in its industrial value.

Claims

1. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus of the type to provide optical pulses shaped in waveform, **characterized in that** it comprises:

an ultra-broadband light pulse generating means for receiving from a light source a fundamental wave light pulse having a bandwidth and broadening the bandwidth of said fundamental wave light pulse into an ultra-broadband range to produce an ultra-broadband light pulse;

a beam expander means for spatially expanding a beam of said ultra-broadband light pulse in a direction in a cross section of said beam to

form an expanded beam of ultra-broadband light pulse; and

a wavelength dispersive means for dispersing wavelengths of the ultra-broadband light pulse of said expanded beam while further spatially expanding said expanded beam in another direction in a cross section thereof, thereby forming an ultra-broadband light pulse with a beam cross section thereof expanded two-dimensionally.

2. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in claim 1, **characterized in that** it further includes:

a two-dimensional spatial amplitude modulator for selecting wavelength bands varying in center frequency along one direction in the ultra-broadband light pulse with the beam cross section expanded two-dimensionally; and
a two-dimensional spatial phase modulator for modulating a plurality of light components so selected by wavelength into different phases, whereby light pulses shaped in waveform and variable and multiple in wavelength are formed.

3. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in claim 1 or claim 2, **characterized in that** it further includes a beam reducing and waveform shaping means for reducing a two-dimensionally amplitude- and phase-modulated ultra-broadband light pulse component in said another direction in a cross section thereof and shaping it into a desired waveform.

4. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in claim 3, **characterized in that** said beam reducing and waveform shaping means comprises at least one of a cylindrical lens and a cylindrical mirror, on the both.

5. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in claim 3, **characterized in that** said beam reducing and waveform shaping means comprises at least one of a diffraction grating and a prism, on the both.

6. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus **characterized in that** an ultra-broadband light pulse generated on the basis of a fundamental wave light pulse from a light source has its beam cross section spatially expanded in one direction, and its wavelengths dispersed in another direction, in said beam

cross section by at least one of a pair of cylindrical lenses and a pair of cylindrical mirrors on the both and by at least one of a diffraction grating and a prism on the both, respectively; the ultra-broadband light pulse having been expanded is collimated by either a cylindrical lens or a cylindrical mirror on the both; the collimated ultra-broadband light pulse is applied to a two-dimensional spatial amplitude modulator for selection of wavelength bands varying in center wavelength along said one direction; and a plurality of light components so selected by wavelength is modulated into different phases, respectively, to produce light pulses shaped in waveform and variable and multiple in wavelength.

7. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in claim 6, **characterized in that** an ultra-broadband light pulse modulated by both said two-dimensional spatial amplitude and phase modulators is reduced in beam cross section by at least one of a cylindrical lens and a cylindrical mirror on the both, or at least one of a diffraction grating and a prism on the both, and thereby is shaped into a desired waveform.

8. An ultra-broadband, variable and multiple wavelength pulse waveform shaping apparatus as set forth in any one of claims 2, 3, 6 and 7, **characterized in that** said two-dimensional spatial amplitude modulator and said two-dimensional spatial phase modulator are each subjected to a feedback control so as to provide desired pulses.

9. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in claim 1 or claim 6, **characterized in that** said light source is a pulse laser generator of providing an ultra-short pulse of pico-seconds or less.

10. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in any one of claims 1, 6 and 9, **characterized in that** said light source for generating said fundamental wave light pulse is any one of a solid state laser, a fiber laser, a semiconductor laser, a dye laser and an optical parametric laser, or a combination thereof with an amplifier system.

11. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in claim 1 or claim 6, **characterized in that** said ultra-broadband light pulse producing means includes at least one nonlinear optical medium adapted for said fundamental wave light pulse to be passed therethrough.

12. An ultra-broadband, variable and multiple wave-

length, pulse waveform shaping apparatus as set forth in any one of claims 1, 6 and 11, **characterized in that** said ultra-broadband light pulse is a light pulse in an ultra-broadband and of pico-seconds or less.

13. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in claim 11, **characterized in that** said nonlinear optical medium is a hollow fiber filled with either a gas or an ionized gas.

14. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in claim 11 or claim 13, **characterized in that** said nonlinear optical medium is made of any one of a waveguide structure, a bulk structure, a thin film structure, a photonic crystalline structure, a photonic fiber and a liquid, or an optical combination of two or more thereof.

15. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in any one of claims 11, 13 and 14, **characterized in that** said nonlinear optical medium has a third-order nonlinear optical property.

16. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in any one of claims 2, 6 and 8, **characterized in that** said two-dimensional spatial amplitude modulator includes a two-dimensional space filter for selecting different center wavelength from the ultra-broadband light pulse.

17. An ultra-broadband, variable and multiple wavelength, pulse waveform shaping apparatus as set forth in any one of claims 2, 6 and 8, **characterized in that** said two-dimensional spatial amplitude modulator comprises a first ultra-broadband polarizing plate, a two-dimensional spatial phase modulator, and a second ultra-broadband polarizing plate whose polarizing axis is perpendicular to the polarizing axis of said first polarizing plate.

FIG. 1




FIG. 2







FIG. 3



(a)



(b)

FIG. 4




FIG. 5




FIG. 6







FIG. 7






(a)



(b)

FIG. 8



INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP00/07699

A. CLASSIFICATION OF SUBJECT MATTER Int.Cl ⁷ G02F 1/01		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) Int.Cl ⁷ G02F 1/01 H01S3/10		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Jitsuyo Shinan Koho 1922-1996 Toroku Jitsuyo Shinan Koho 1994-2001 Kokai Jitsuyo Shinan Koho 1971-2001 Jitsuyo Shinan Toroku Koho 1996-2001		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) JICST USPTO Web Patent Database , esp@cenet WPI		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, 5682262, A (Massachusetts Institute of Technology), 28 October, 1997 (28.10.97), Full text; Figs. 1 to 5 (Family: none)	1-17
A	JP, 02-012227, A (HAMAMATSU PHOTONICS K.K.), 17 January, 1990 (17.01.90), Full text; Figs. 1 to 10 (Family: none)	1-17
A	Mikio YAMASHITA, "Femto Byou Hikari Pulse no Hassei to Seigyo", O plus E, No.176, (July, 1994), pp.76-83	1-17
A	US, 5263039, A (The University of Rochester), 16 November, 1993 (16.11.93), Full text; Figs. 1 to 5 (Family: none)	1-17
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>		
Date of the actual completion of the international search 30 January, 2001 (30.01.01)		Date of mailing of the international search report 13 February, 2001 (13.02.01)
Name and mailing address of the ISA/ Japanese Patent Office		Authorized officer
Facsimile No.		Telephone No.

Form PCT/ISA/210 (second sheet) (July 1992)